

Surelock 'Slimline' Key Driven Enhancement Codes

Slimline Entry/Exit Codes							Enhancement Descriptions
Deadlocking							
Code	01	10	11	13	14*	15*	
† A0	✓	✓	✓	✓			Manual bolting
† A3	✓	✓	✓	✓		✓	Auto-bolting sliding doors
A5	✓	✓	✓	✓	✓	✓	Auto-bolting - traditional trigger (grey/white finish)
B(n)	✓	✓	✓	✓	✓	✓	Packing; (n) = number of 1mm increments
† E(n)	✓	✓	✓	✓	✓	✓	Height increment above 2500mm; (n) = number of 500mm increments
† H0	✓	✓	✓	✓			Handle(s) not included
H3						✓	Push pad; in place of inside handle
H6	sp		sp				Panic bar in lieu of standard internal operation
H9			✓	✓			Handles not included; with 8mm follower
H11	◆		◆		✓		1M long panic bar tube
H12	✓		✓	✓		✓	Red flat lever inside handle
H14						✓	St/St lever handle inside in lieu of green handle
K	◆	◆	◆	◆			Key retained in unlocked position
K0	✓	✓	✓	✓	✓	✓	Manual locking
K4				✓			Break-dome facility over turnknob
K6	✓		✓				Lockable with the bolts in the retracted position only
K7	✓		✓				Lock back facility addition, bolts secured in thrown and retracted position
K12	✓	✓	✓	✓	✓	✓	Euro-profile cylinder in place of standard external rim-latch cylinder
K15				✓			Shrouded internal turnknob release
M	✓	✓	✓	✓	✓	✓	Electric monitoring of bolt status
N	✓	✓	✓	✓	✓	✓	Electric monitoring of lock status
O0	✓	✓	✓	✓	✓	✓	Cylinder - supplied free -issue (approved types and factory fitted only)
O1	✓	✓	✓	✓	✓	✓	Cylinder - Kaba-20 (registered)
O2	✓	✓	✓	✓	✓	✓	Cylinder - Assa Twin Combi 5800 (registered)
O3	✓	✓	✓	✓	✓	✓	Cylinder - Yale
O4	✓	✓	✓	✓	✓	✓	Cylinder - Bramah (registered)
O5	✓	✓	✓	✓	✓	✓	Cylinder - Medeco ARX (registered)
O6	✓	✓	✓	✓	✓	✓	Cylinder - Ingersoll (registered)
O8	*	*	*	*	*	*	Cylinder - Union 5-pin (non-registered)
O9	✓	✓	✓	✓	✓	✓	Cylinder - Abloy Disklock Pro cylinder (registered, gold level)
O10	✓	✓	✓	✓	✓	✓	Cylinder - Kaba Quattro S (registered)
O11	✓	✓	✓	✓	✓	✓	Cylinder - Kaba 20 Armoured 'C5' (registered)
O22	✓	✓	✓	✓	✓	✓	Cylinder - Assa Ruko Flexcore (choice for registration)
O91	✓	✓	✓	✓	✓	✓	Cylinder - Abloy Protec (registered, diamond level)
P		✓	✓	✓	✓	✓	Cylinder guard for door thickness 44-60mm - tested to LPS1175 rating 3 protection
P2		◆	◆	◆	◆	◆	Cylinder guard S-8374 for door thickness of 50 to 56mm only suitable for Ingersoll cylinder option 06
P3		◆	◆	◆	◆	◆	Cylinder guard S-8374 for door thickness of 44 to 49mm only suitable for Ingersoll cylinder option 06
P4		◆	◆	◆	◆	◆	Cylinder guard to take Euro profile cylinder
P5		✓	✓	✓	✓	✓	Cylinder guard for door thickness 44-60mm - tested to LPS1175 rating 4 protection
Q1		✓	✓	✓	◆	◆	Twin lock (additional lock below handle) - locked in thrown and retracted key retained in unlocked position. 90° key operation.
Q6		✓	✓	✓	◆	◆	Secondary manual key operated deadlock (2-man entry); panic or emergency exit (if selected) overrides both locks
S	✓	✓	✓	✓	✓	✓	Stainless steel 316 - finish polished
T	✓	✓	✓	✓	✓	✓	Slave unit, 90 deg. below handle
T1	✓	✓	✓	✓	✓	✓	Slave unit, 90 deg. above handle
U	✓	✓	✓	✓	✓	✓	Slave unit, 90 deg. & continue, below handle
U1	✓	✓	✓	✓	✓	✓	Slave unit, 90 deg. & continue, above handle
W	✓	✓	✓	✓	✓	✓	Machine screws with steel dowels
W2	✓	✓	✓	✓	✓	✓	Surface fixing by coach screws
W3	✓	✓	✓	✓	✓	✓	Surface fixing by machine screws
W5	✓	✓	✓	✓	✓	✓	Surface fixing by security screws - timber doors & frames
W6	✓	✓	✓	✓	✓	✓	Surface fixing by security screws - steel doors & frames
W8	✓	✓	✓	✓	✓	✓	Mortice fixing pack with guides - timber doors
W9	✓	✓	✓	✓	✓	✓	Mortice fixing pack with guides - steel doors
Y0					✓		BSEN non type approved device
Z1					✓	✓	Double door leaf - BSEN type approved device (active leaf only)
Z2					✓	✓	Double door leaf - BSEN non type approved device - interlink panic bar/push pad (both leaves)

- ✓ Available enhancements
- ◆ Dependant on other enhancement(s)
- ✓ Popular enhancements

† Options non-conformant with BSEN 179 and BS EN 1125 certification

* Handing required

Handing chart

