

Slimline Panic and Emergency Exit Enhancement Codes

		Slimline Entry/Exit Codes		Enhancement Descriptions
		Bolting		
Code	04	05		
†	A0		◆	Manual bolting
†	A3		✓	Auto-bolting sliding doors
	A5	✓	✓	Auto-bolting - traditional trigger (grey/white finish)
	B(n)	✓	✓	Packing; (n) = number of 1mm increments
†	E(n)	✓	✓	Height increment above 2500mm; (n) = number of 500mm increments
	H	✓	✓	External stainless steel lever handle addition (non lockable)
†	H0		◆	Handle(s) not included
	H3		✓	Push pad; in place of inside handle
	H8	✓	✓	External pad-lockable handle with emergency override (padlock not supplied)
	H11	✓		1M long panic bar tube
	H12		✓	Red flat lever inside handle
	H14		✓	St/St lever handle inside in lieu of green handle
	K	◆	◆	Key retained in unlocked position
	K8	✓	✓	Automatic locking upon bolt retraction - internal key re-set facility
	K14	✓	✓	Manual deadlock with bolts in retracted position only (Euro-profile cylinder)
*	L	✓	✓	LEO - external key-entry lock with internal emergency override - surface mounted
*	L0		◆	As 'L' but with manual securing of bolts (non auto-bolting)
*	L1	✓	✓	Recessed LEO (flush fitting) - tested to LPS 1175 rating 3 protection
*	L2	✓	✓	Recessed LEO (flush fitting) with cylinder guard - tested to LPS 1175 rating 4 protection
*	L10		◆	As 'L1' but with manual securing of bolts (non auto-bolting)
*	L20		◆	As 'L2' but with manual securing of bolts (non auto-bolting)
	M	✓	✓	Electric monitoring of bolt status
	N	◆	◆	Electric monitoring of lock status
	O0	◆	◆	Cylinder - supplied free - issue (approved types and factory fitted only)
	O1	◆	◆	Cylinder - Kaba-20 (registered)
	O2	◆	◆	Cylinder - Assa Twin Combi 5800 (registered)
	O3	◆	◆	Cylinder - Yale
	O4	◆	◆	Cylinder - Bramah (registered)
	O5	◆	◆	Cylinder - Medeco ARX (registered)
	O8	◆	◆	Cylinder - Union 5-pin (non-registered)
	O9	◆	◆	Cylinder - Abloy Disklock Pro cylinder (registered, gold level)
	O10	◆	◆	Cylinder - Kaba Quattro S (registered)
	O11	◆	◆	Cylinder - Kaba 20 Armoured 'C5' (registered)
	O22	◆	◆	Cylinder - Assa Ruko Flexcore (choice for registration)
	O91	◆	◆	Cylinder - Abloy Protec (registered, diamond level)
	Q4	✓	✓	Resistance to bolt end-thrust attack
	S	✓	✓	Stainless steel 316 - finish polished
	T	✓	✓	Slave unit, 90 deg. below handle
	T1	✓	✓	Slave unit, 90 deg. above handle
	U	✓	✓	Slave unit, 90 deg. & continue, below handle
	U1	✓	✓	Slave unit, 90 deg. & continue, above handle
*	V	✓	✓	VIP (Visual Indicator Panel)
*	V1	✓	✓	VIP (Visual Indicator Panel) with electric monitoring of indicator & isolation keyswitch
*	V2	✓	✓	VIP (Visual Indicator Panel) with electric monitoring of indicator
	W	✓	✓	Machine screws with steel dowels
	W2	✓	✓	Surface fixing by coach screws
	W3	✓	✓	Surface fixing by machine screws
	W5	✓	✓	Surface fixing by security screws - timber doors & frames
	W6	✓	✓	Surface fixing by security screws - steel doors & frames
	W8	✓	✓	Mortice fixing pack with guides - timber doors
	W9	✓	✓	Mortice fixing pack with guides - steel doors
	Y0	✓	✓	BSEN non type approved device
	Z1	✓	✓	Double door leaf - BSEN type approved device (active leaf only)
	Z2	✓	✓	Double door leaf - BSEN non type approved device - interlink panic bar/push pad (both leaves)

✓	Available enhancements
◆	Dependant on other enhancement(s)
✓	Popular enhancements

† Options non-conformant with BSEN 179 and BS EN 1125 certification

* Handing required

Handing chart

